




## Plastlok Assembly

**Easy to adjust Foot** | Handle irregularities on the floor by adjusting the foot.

Easy adjustable shelving | If you want to adjust the shelves, remove the shelf inserts and add/remove traverses as per requirement. No need to disassemble the whole unit. Shelves can be adjusted in 100mm increments.

DO NOT USE A METAL HAMMER, PLEASE TRY TO USE A RUBBER MALLET TO ENSURE PROPER ASSEMBLY



Step 1 | Connect two posts using a set of post connectors, according to the direction of the arrows. (A set include a top and bottom post connection). Repeat for second side of unit. (Fig. 1)




Fig. 3



ep 2 | Centre the bott

Step 2 | Centre the bottom of the traverse dovetails with the dovetails on the posts, according to the length of traverses. Slide smoothly into position. (Fig. 2). Please align as shown in this photo above, then let the traverse slide to dovetail.





Step 4 | Add an additional unit by connecting two more posts with post connectors and then setting traverses onto the dovetails on the posts. The traverses on the first and second unit share the middle post. Place shelf plates on traverses to complete the second unit. Add an additional unit in a 90° corner using corner connectors. (Fig. 4)

P: 0508 668 256 E: SALES@NOVALOK.CO.NZ W: WWW.NOVALOK.CO.NZ